

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 1 of 19

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

ATORN BRIGHT ZINC 400ML

### SYNONYMS

"Manufacturer's Code .69368"

### PROPER SHIPPING NAME

AEROSOLS

### PRODUCT USE

■ Application is by spray atomisation from a hand held aerosol pack.  
Used for protection of metal surfaces.

### SUPPLIER

Company: Thomas Warburton Pty Ltd

Address:

16- 26 Dunlop Road

Mulgrave

VIC, 3170

AUS

Telephone: +61 3 9574 3400

Emergency Tel: +61 3 9547 3400

Fax: +61 3 9574 3456

---

## Section 2 - HAZARDS IDENTIFICATION

---

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.**

### POISONS SCHEDULE

None

### RISK

- Extremely flammable.
- Harmful by inhalation.
- Irritating to eyes.
- Risk of explosion if heated under confinement.
- Vapours may cause drowsiness and dizziness.

### SAFETY

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/ fumes/ vapour/ spray.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
  
- Avoid exposure - obtain special instructions before use.
  
- To clean the floor and all objects contaminated by this material use water and detergent.
- Keep container tightly closed.
- Keep away from food drink and animal feeding stuffs.
- In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
- If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).
- This material and its container must be disposed of as hazardous waste.

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 2 of 19

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
acetone	67-64-1	1-19
ethyl acetate	141-78-6	1-19
xylene	1330-20-7	1-12.4
naphtha petroleum, heavy, hydrotreated	64742-48-9.	1-9
n- butyl acetate	123-86-4	1-10
aluminium	7429-90-5	1-10
n- butanol	71-36-3	1-4
propellant, as dimethyl ether	115-10-6	30-60

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- Not considered a normal route of entry.
- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

### EYE

- If aerosols come in contact with the eyes:
  - Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Transport to hospital or doctor without delay.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If solids or aerosol mists are deposited upon the skin:
  - Flush skin and hair with running water (and soap if available).
  - Remove any adhering solids with industrial skin cleansing cream.
  - DO NOT use solvents.
  - Seek medical attention in the event of irritation.

### INHALED

- If aerosols, fumes or combustion products are inhaled:
  - Remove to fresh air.
  - Lay patient down. Keep warm and rested.
  - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
  - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
  - Transport to hospital, or doctor.

### NOTES TO PHYSICIAN

- Treat symptomatically.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 3 of 19  
Section 4 - FIRST AID MEASURES

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology].

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

#### ■ SMALL FIRE:

- Water spray, dry chemical or CO<sub>2</sub>

#### LARGE FIRE:

- Water spray or fog.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

### FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- Aerosol cans may explode on exposure to naked flame.
- Rupturing containers may rocket and scatter burning materials.
- Hazards may not be restricted to pressure effects.
- May emit acrid, poisonous or corrosive fumes.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

WARNING: In use may form flammable/ explosive vapour-air mixtures.

Combustion products include: carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.

### FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0

CD 2009/3 Page 4 of 19

Section 5 - FIRE FIGHTING MEASURES

HAZCHEM: 2YE

## Personal Protective Equipment

Gas tight chemical resistant suit.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Wipe up.
- If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.

### MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Absorb or cover spill with sand, earth, inert materials or vermiculite.
- If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.
- Collect residues and seal in labelled drums for disposal.

### EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

n-butyl acetate 3000ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

n-butyl acetate 200ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

n-butyl acetate 5ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 5 of 19

## Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

### STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storing and handling recommendations.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	Notes
Australia Exposure Standards	acetone (Acetone)	500	1185	1000	2375			
Australia	ethyl acetate	200	720	400	1440			

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
 Issue Date: 17-Nov-2009  
 NC317ECP

CHEMWATCH 4744-39  
 Version No:2.0  
 CD 2009/3 Page 6 of 19

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	Notes
Exposure Standards	(Ethyl acetate)							
Australia Exposure Standards	naphtha petroleum, heavy, hydrotreated (Petrol (gasoline))		900					(see Chapter 16)
Australia Exposure Standards	n- butyl acetate (n- Butyl acetate)	150	713	200	950			
Australia Exposure Standards	aluminium (Aluminium (welding fumes) (as Al))		5					
Australia Exposure Standards	aluminium (Aluminium (metal dust))		10					
Australia Exposure Standards	n- butanol (n- Butyl alcohol)					50	152	Sk
Australia Exposure Standards	dimethyl ether (Dimethyl ether)	400	760	500	950			

### EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m <sup>3</sup> )	Revised IDLH Value (ppm)
acetone		2, 500 [LEL]
ethyl acetate		2, 000 [LEL]
xylene		900

### NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

### MATERIAL DATA

ATORN BRIGHT ZINC 400ML:  
 Not available

### ACETONE:

- Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures. The NIOSH REL-TWA is substantially lower and has taken into account slight irritation experienced by volunteer subjects at 300 ppm. Mild irritation to acclimatised workers begins at about 750 ppm - unacclimatised subjects will experience irritation at about 350-500 ppm but acclimatisation can occur rapidly. Disagreement between the peak bodies is based largely on the view by ACGIH that widespread use of acetone, without evidence of significant adverse health effects at higher concentrations, allows acceptance of a higher limit.

Half-life of acetone in blood is 3 hours which means that no adjustment for shift-length has to be made with reference to the standard 8 hour/day, 40 hours per week because body clearance occurs within any shift

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 7 of 19

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

with low potential for accumulation.

A STEL has been established to prevent excursions of acetone vapours that could cause depression of the central nervous system.

Odour Safety Factor(OSF)

OSF=38 (ACETONE).

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

### ETHYL ACETATE:

■ For ethyl acetate:

Odour Threshold Value: 6.4-50 ppm (detection), 13.3-75 ppm (recognition)

The TLV-TWA provides a significant margin of safety from the standpoint of adverse health effects.

Unacclimated subjects found the odour objectionably strong at 200 ppm. Mild nose, eye and throat irritation was experienced at 400 ppm. Workers exposed regularly at concentrations ranging from 375 ppm to 1500 ppm for several months showed no unusual signs or symptoms.

Odour Safety Factor(OSF)

OSF=51 (ETHYL ACETATE).

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 8 of 19

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

D	0.18- 1	persons being distracted 10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

### XYLENE:

#### ■ for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

Xylene vapour is an irritant to the eyes, mucous membranes and skin and causes narcosis at high concentrations. Exposure to doses sufficiently high to produce intoxication and unconsciousness also produces transient liver and kidney toxicity. Neurologic impairment is NOT evident amongst volunteers inhaling up to 400 ppm though complaints of ocular and upper respiratory tract irritation occur at 200 ppm for 3 to 5 minutes.

Exposure to xylene at or below the recommended TLV-TWA and STEL is thought to minimise the risk of irritant effects and to produce neither significant narcosis or chronic injury. An earlier skin notation was deleted because percutaneous absorption is gradual and protracted and does not substantially contribute to the dose received by inhalation.

Odour Safety Factor(OSF)

OSF=4 (XYLENE).

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

## PERSONAL PROTECTION

### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### HANDS/FEET

- No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.
- For potentially heavy exposures:
- Wear chemical protective gloves, eg. PVC. and safety footwear.

### OTHER

- No special equipment needed when handling small quantities.
- OTHERWISE:
- Overalls.

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 9 of 19

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.

### RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AX- AUS	-
1000	50	-	AX- AUS
5000	50	Airline *	-
5000	100	-	AX- 2
10000	100	-	AX- 3
	100+		Airline**

\* - Continuous Flow

\*\* - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

### ENGINEERING CONTROLS

■ General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.

Provide adequate ventilation in warehouse or closed storage areas.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

■ Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable ether propellant. Silver coloured liquid with a characteristic odour; does not mix with water.

### PHYSICAL PROPERTIES

Liquid.

Gas.

Does not mix with water.

Molecular Weight: Not  
Applicable

Specific Gravity (water=1):  
0.9- 1.1

pH (1% solution): Not  
Applicable

Evaporation Rate: Not Available

Lower Explosive Limit (%): 0.6  
Decomposition Temp (°C): Not  
Available

Boiling Range (°C): 55 approx.

Solubility in water (g/L):  
Immiscible

Vapour Pressure (kPa): Not Available

Relative Vapour Density (air=1): Not  
Available

Upper Explosive Limit (%): 13  
State: Liquid

Melting Range (°C): Not  
Available

pH (as supplied): Not  
Applicable

Volatile Component (%vol):  
>60

Flash Point (°C): - 19  
approx.

Autoignition Temp (°C): 240  
Viscosity: Not Available

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 10 of 19

---

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

*For incompatible materials - refer to Section 7 - Handling and Storage.*

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

- Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

##### EYE

- The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

##### SKIN

- Spray mist may produce discomfort.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

- Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. Vapour is heavier than air and may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

Inhalation of freshly formed zinc oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever", with symptoms resembling influenza. Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalised feeling of malaise. Mild to severe headache, nausea, occasional vomiting, fever or chills, exaggerated mental activity, profuse sweating, diarrhoea, excessive urination and prostration may also occur. Tolerance to the fumes develops rapidly, but is quickly lost. All symptoms usually subside within 24-36 hours following removal from exposure. Leucocytosis, a transient increase in white blood cell counts, is reported as a common finding in metal fume fever but is not known to be common amongst welders. Severe over-exposure to zinc oxide, following inhalation of fumes or finely divided dusts may result in bronchitis or pneumonia; a bluish skin tint may be present.

Ketone vapours irritate the nose, throat and mucous membrane. High concentrations depress the central nervous system, causing headache, vertigo, poor concentration, sleep and failure of the heart and breathing. Some ketones can cause multiple nerve disorders, inducing "pins and needles" and weakness in the limbs.

Inhalation of acetone causes central nervous system depression, light-headedness, incoherent speech, inco-ordination, stupor, low blood pressure, fast pulse, metabolic acidosis, high blood sugar and ketosis. Rarely, convulsions and tubular necrosis may be evident. Other symptoms of exposure may include restlessness, headache, vomiting, low blood pressure and rapid and irregular pulse, eye and throat irritation, weakness of the legs and dizziness. Inhalation of high concentrations may produce dryness of the mouth and throat, nausea,

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 11 of 19

## Section 11 - TOXICOLOGICAL INFORMATION

inco-ordinated movement, loss of co-ordinated speech, drowsiness, and in severe cases, coma. Inhalation of acetone vapours over long periods causes irritation of the airways, coughing and headache. Rats exposed to a concentration of 5.22% for 1 hour showed clear signs of sleepiness; deaths occurred at 12.66%.

### CHRONIC HEALTH EFFECTS

■ Principal route of occupational exposure to the gas is by inhalation.

Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

WARNING: Aerosol containers may present pressure related hazards.

### TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

#### ACETONE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

#### TOXICITY

Oral (man) TDLo: 2857 mg/kg

Oral (rat) LD50: 5800 mg/kg

Inhalation (human) TCLo: 500 ppm

Inhalation (man) TCLo: 12000 ppm/4 hr

Inhalation (man) TCLo: 10 mg/m<sup>3</sup>/6 hr

Inhalation (rat) LC50: 50100 mg/m<sup>3</sup>/8 hr

Dermal (rabbit) LD50: 20000 mg/kg

■ The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

for acetone:

The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitiser but is a defatting agent to the skin. Acetone is an eye irritant. The subchronic toxicity of acetone has been examined in mice and rats that were administered acetone in the drinking water and again in rats treated by oral gavage. Acetone-induced increases in relative kidney weight changes were observed in male and female rats used in the oral 13-week study. Acetone treatment caused increases in the relative liver weight in male and female rats that were not associated with histopathologic effects and the effects may have been associated with microsomal enzyme induction. Haematologic effects consistent with macrocytic anaemia were also noted in male rats along with hyperpigmentation in the spleen. The most notable findings in the mice were increased liver and decreased spleen weights. Overall, the no-observed-effect-levels in the drinking water study were 1% for male rats (900 mg/kg/d) and male mice (2258 mg/kg/d), 2% for female mice (5945 mg/kg/d), and 5% for female rats (3100 mg/kg/d). For developmental effects, a statistically significant reduction in foetal weight, and a slight, but statistically significant increase in the percent incidence of later resorptions were seen in mice at 15, 665 mg/m<sup>3</sup> and in rats at 26,100 mg/m<sup>3</sup>. The no-observable-effect level for developmental toxicity was determined to be 5220 mg/m<sup>3</sup> for both rats and mice.

Teratogenic effects were not observed in rats and mice tested at 26,110 and 15,665 mg/m<sup>3</sup>, respectively.

Lifetime dermal carcinogenicity studies in mice treated with up to 0.2 mL of acetone did not reveal any increase in organ tumor incidence relative to untreated control animals.

The scientific literature contains many different studies that have measured either the neurobehavioural performance or neurophysiological response of humans exposed to acetone. Effect levels ranging from about 600 to greater than 2375 mg/m<sup>3</sup> have been reported. Neurobehavioral studies with acetone-exposed employees have recently shown that 8-hr exposures in excess of 2375 mg/m<sup>3</sup> were not associated with any dose-related changes in response time, vigilance, or digit span scores. Clinical case studies, controlled human volunteer studies, animal research, and occupational field evaluations all indicate that the NOAEL for this effect is 2375 mg/m<sup>3</sup> or greater.

#### ETHYL ACETATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 12 of 19

## Section 11 - TOXICOLOGICAL INFORMATION

### TOXICITY

Oral (rat) LD50: 5620 mg/kg  
Inhalation (rat) LC50: 1600 ppm/8h  
Inhalation (human) TClO: 400 ppm  
Inhalation (Human) TClO: 400 ppm/4h  
Oral (Mouse) LD50: 4100 mg/kg  
Intraperitoneal (Mouse) LD50: 709 mg/kg  
Oral (Rabbit) LD50: 4935 mg/kg  
Oral (Guinea pig) LD50: 5500 mg/kg

### IRRITATION

Eye (human): 400 ppm

### XYLENE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

### TOXICITY

Oral (human) LDLo: 50 mg/kg  
Oral (rat) LD50: 4300 mg/kg  
Inhalation (human) TClO: 200 ppm  
Inhalation (man) LCLo: 10000 ppm/6h  
Inhalation (rat) LC50: 5000 ppm/4h  
Oral (Human) LD: 50 mg/kg  
Inhalation (Human) TClO: 200 ppm/4h  
Intraperitoneal (Rat) LD50: 2459 mg/kg  
Subcutaneous (Rat) LD50: 1700 mg/kg  
Oral (Mouse) LD50: 2119 mg/kg  
Intraperitoneal (Mouse) LD50: 1548 mg/kg  
Intravenous (Rabbit) LD: 129 mg/kg  
Inhalation (Guinea) pig: LC 450 ppm/4h

### IRRITATION

Skin (rabbit):500 mg/24h Moderate  
Eye (human): 200 ppm Irritant  
Eye (rabbit): 87 mg Mild  
Eye (rabbit): 5 mg/24h SEVERE

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Reproductive effector in rats

### CARCINOGEN

Xylenes	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3
---------	---	-------	---

### REPROTOXIN

xylene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility
--------	--	-----------------------------------

## Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

ATORN BRIGHT ZINC 400ML:

XYLENE:

■ Harmful to aquatic organisms.

ATORN BRIGHT ZINC 400ML:

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 13 of 19

Section 12 - ECOLOGICAL INFORMATION

XYLENE:

ETHYL ACETATE:

ACETONE:

- DO NOT discharge into sewer or waterways.

ATORN BRIGHT ZINC 400ML:

Marine Pollutant: Not Determined

Water hazard class 2 (Self-assessment): hazardous to water.

ACETONE:

■ Fish LC50 (96hr.) (mg/l):	8300- 40000
■ Daphnia magna EC50 (48hr.) (mg/l):	10
■ log Kow (Prager 1995):	- 0.24
■ log Kow (Sangster 1997):	- 0.24
■ log Pow (Verschueren 1983):	- 0.24
■ BOD5:	122%
■ ThOD:	72
■ Half- life Soil - High (hours):	168
■ Half- life Soil - Low (hours):	24
■ Half- life Air - High (hours):	2790
■ Half- life Air - Low (hours):	279
■ Half- life Surface water - High (hours):	168
■ Half- life Surface water - Low (hours):	24
■ Half- life Ground water - High (hours):	336
■ Half- life Ground water - Low (hours):	48
■ Aqueous biodegradation - Aerobic - High (hours):	168
■ Aqueous biodegradation - Aerobic - Low (hours):	24
■ Aqueous biodegradation - Anaerobic - High (hours):	672
■ Aqueous biodegradation - Anaerobic - Low (hours):	96
■ Aqueous biodegradation - Removal secondary treatment - High (hours):	75%
■ Aqueous biodegradation - Removal secondary treatment - Low (hours):	54%
■ Aqueous photolysis half- life - High (hours):	270
■ Photooxidation half- life water - High (hours):	3.97E+06
■ Photooxidation half- life water - Low (hours):	9.92E+04
■ Photooxidation half- life air - High (hours):	2790
■ Photooxidation half- life air - Low (hours):	279

■ For ketones:

Ketones, unless they are alpha, beta--unsaturated ketones, can be considered as narcosis or baseline toxicity compounds

Hydrolysis may also involve the addition of water to ketones to yield ketals under mild acid conditions.

However, this addition of water is thermodynamically favorable only for low molecular weight ketones. This addition is an equilibrium reaction that is reversible upon a change of water concentration and the reaction ultimately leads to no permanent change in the structure of the ketone substrate. The higher molecular weight ketones do not form stable ketals. Therefore, the ketones are stable to water under ambient environmental conditions

Another possible reaction of ketones in water involves the enolic hydrogen on the carbons bonded to the carbonyl function. Under conditions of high pH (pH greater than 10), the enolic proton is abstracted by base (OH-) forming a carbanion intermediate that may react with other organic substrates (e.g., ketones, esters, aldehydes) containing a center for nucleophilic attack. The reactions, commonly recognized as condensation reactions, produce higher molecular weight products. Under ambient conditions of temperature, pH, and low concentration, these condensation reactions are unfavorable.

Based on its reactions in air, it seems likely that ketones undergo photolysis in water. It is probable that ketones will be biodegraded to an appreciable degree by micro-organisms in soil and water. They are unlikely to bioconcentrate or biomagnify.

■ for acetone:

log Kow: -0.24

Half-life (hr) air: 312-1896

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 14 of 19

Section 12 - ECOLOGICAL INFORMATION

Half-life (hr) H<sub>2</sub>O surface water: 20

Henry's atm m<sup>3</sup> /mol: 3.67E-05

BOD 5: 0.31-1.76,46-55%

COD: 1.12-2.07

ThOD: 2.2

BCF: 0.69

Environmental fate:

Acetone preferentially locates in the air compartment when released to the environment. A substantial amount of acetone can also be found in water, which is consistent with the high water to air partition coefficient and its small, but detectable, presence in rain water, sea water, and lake water samples. Very little acetone is expected to reside in soil, biota, or suspended solids. This is entirely consistent with the physical and chemical properties of acetone and with measurements showing a low propensity for soil absorption and a high preference for moving through the soil and into the ground water

In air, acetone is lost by photolysis and reaction with photochemically produced hydroxyl radicals; the estimated half-life of these combined processes is about 22 days. The relatively long half-life allows acetone to be transported long distances from its emission source.

Acetone is highly soluble and slightly persistent in water, with a half-life of about 20 hours; it is minimally toxic to aquatic life.

Acetone released to soil volatilises although some may leach into the ground where it rapidly biodegrades.

Acetone does not concentrate in the food chain.

Acetone meets the OECD definition of readily biodegradable which requires that the biological oxygen demand (BOD) is at least 70% of the theoretical oxygen demand (THOD) within the 28-day test period

Drinking Water Standard: none available.

Soil Guidelines: none available.

Air Quality Standards: none available.

Ecotoxicity:

Testing shows that acetone exhibits a low order of toxicity

Fish LC<sub>50</sub>: brook trout 6070 mg/l; fathead minnow 15000 mg/l

Bird LC<sub>0</sub> (5 day): Japanese quail, ring-neck pheasant 40,000 mg/l

Daphnia magna LC<sub>50</sub> (48 h): 15800 mg/l; NOEC 8500 mg/l

Aquatic invertebrate 2100 - 16700 mg/l

Aquatic plant NOEC: 5400-7500 mg/l

Daphnia magna chronic NOEC 1660 mg/l

Acetone vapors were shown to be relatively toxic to two types insects and their eggs. The time to 50% lethality (LT<sub>50</sub>) was found to be 51.2 hr and 67.9 hr when the flour beetle (*Tribolium confusum*) and the flour moth (*Ephestia kuehniella*) were exposed to an airborne acetone concentration of 61.5 mg/m<sup>3</sup>. The LT<sub>50</sub> values for the eggs were 30-50% lower than for the adult. The direct application of acetone liquid to the body of the insects or surface of the eggs did not, however, cause any mortality.

The ability of acetone to inhibit cell multiplication has been examined in a wide variety of microorganisms.

The results have generally indicated mild to minimal toxicity with NOECs greater than 1700 mg/L for exposures lasting from 6 hr to 4 days. Longer exposure periods of 7 to 8 days with bacteria produced mixed results; but overall the data indicate a low degree of toxicity for acetone. The only exception to these findings were the results obtained with the flagellated protozoa (*Entosiphon sulcatum*) which yielded a 3-day NOEC of 28 mg/L.

ETHYL ACETATE:

■ log Pow (Verschueren 1983):	0.66/0.73
■ ThOD:	50.4
■ log Pow (Verschueren 1983):	0.66/0.73
■ BOD <sub>5</sub> :	15%
■ COD:	1.54 (83%)
■ ThOD:	1.82
■ Half- life Soil - High (hours):	168
■ Half- life Soil - Low (hours):	24
■ Half- life Air - High (hours):	353
■ Half- life Air - Low (hours):	35.3
■ Half- life Surface water - High (hours):	168
■ Half- life Surface water - Low (hours):	24
■ Half- life Ground water - High (hours):	336
■ Half- life Ground water - Low (hours):	48

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 15 of 19

## Section 12 - ECOLOGICAL INFORMATION

■ Aqueous biodegradation - Aerobic - High (hours):	168
■ Aqueous biodegradation - Aerobic - Low (hours):	24
■ Aqueous biodegradation - Anaerobic - High (hours):	672
■ Aqueous biodegradation - Anaerobic - Low (hours):	96
■ Aqueous biodegradation - Removal secondary treatment - High (hours):	96%
■ Aqueous biodegradation - Removal secondary treatment - Low (hours):	99.90%
■ Photooxidation half- life water - High (hours):	9.60E+05
■ Photooxidation half- life water - Low (hours):	24090
■ Photooxidation half- life air - High (hours):	353
■ Photooxidation half- life air - Low (hours):	35.3
■ First order hydrolysis half- life (hours):	1.77E+04
■ Acid rate constant [M(H+)- HR]- 1:	3.05E- 08
■ Base rate constant [MOH]- HR]- 1:	2.99E- 05

log Kow: 0.66-0.73

Half-life (hr) air: 200

Half-life (hr) H2O surface water: 10

Henry's atm m<sup>3</sup>/mol: 1.20E-04

BOD 5 if unstated: 0.1-1.24,16-36%

COD: 1.54,83%

ThOD: 1.82

### XYLENE:

■ Fish LC50 (96hr.) (mg/l):	13.5
■ BCF<100:	2.14- 2.20
■ log Kow (Prager 1995):	3.12- 3.20
■ Half- life Soil - High (hours):	672
■ Half- life Soil - Low (hours):	168
■ Half- life Air - High (hours):	44
■ Half- life Air - Low (hours):	2.6
■ Half- life Surface water - High (hours):	672
■ Half- life Surface water - Low (hours):	168
■ Half- life Ground water - High (hours):	8640
■ Half- life Ground water - Low (hours):	336
■ Aqueous biodegradation - Aerobic - High (hours):	672
■ Aqueous biodegradation - Aerobic - Low (hours):	168
■ Aqueous biodegradation - Anaerobic - High (hours):	8640
■ Aqueous biodegradation - Anaerobic - Low (hours):	4320
■ Photolysis maximum light absorption - High (nano- m):	269.5
■ Photolysis maximum light absorption - Low (nano- m):	265
■ Photooxidation half- life water - High (hours):	2.70E+08
■ Photooxidation half- life water - Low (hours):	3.90E+05
■ Photooxidation half- life air - High (hours):	44
■ Photooxidation half- life air - Low (hours):	2.6

■ For xylenes :

log Koc : 2.05-3.08

Koc : 25.4-204

Half-life (hr) air : 0.24-42

Half-life (hr) H2O surface water : 24-672

Half-life (hr) H2O ground : 336-8640

Half-life (hr) soil : 52-672

Henry's Pa m<sup>3</sup> /mol: 637-879

Henry's atm m<sup>3</sup> /mol: 7.68E-03

BOD 5 if unstated: 1.4,1%

COD : 2.56,13%

ThOD : 3.125

BCF : 23

log BCF : 1.17-2.41

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 16 of 19

Section 12 - ECOLOGICAL INFORMATION

## Environmental Fate

**Terrestrial fate:** Measured Koc values of 166 and 182, indicate that 3-xylene is expected to have moderate mobility in soil. Volatilisation of p-xylene is expected to be important from moist soil surfaces given a measured Henry's Law constant of  $7.18 \times 10^{-3}$  atm-cu m/mole. The potential for volatilisation of 3-xylene from dry soil surfaces may exist based on a measured vapor pressure of 8.29 mm Hg. p-Xylene may be degraded during its passage through soil). The extent of the degradation is expected to depend on its concentration, residence time in the soil, the nature of the soil, and whether resident microbial populations have been acclimated. p-Xylene, present in soil samples contaminated with jet fuel, was completely degraded aerobically within 5 days. In aquifer studies under anaerobic conditions, p-xylene was degraded, usually within several weeks, with the production of 3-methylbenzylfumaric acid, 3-methylbenzylsuccinic acid, 3-methylbenzoate, and 3-methylbenzaldehyde as metabolites.

**Aquatic fate:** Koc values indicate that p-xylene may adsorb to suspended solids and sediment in water. p-Xylene is expected to volatilise from water surfaces based on the measured Henry's Law constant. Estimated volatilisation half-lives for a model river and model lake are 3 hours and 4 days, respectively. BCF values of 14.8, 23.4, and 6, measured in goldfish, eels, and clams, respectively, indicate that bioconcentration in aquatic organisms is low. p-Xylene in water with added humic substances was 50% degraded following 3 hours irradiation suggesting that indirect photooxidation in the presence of humic acids may play an important role in the abiotic degradation of p-xylene. Although p-xylene is biodegradable and has been observed to degrade in pond water, there are insufficient data to assess the rate of this process in surface waters. p-Xylene has been observed to degrade in anaerobic and aerobic groundwater in several studies; however, it is known to persist for many years in groundwater, at least at sites where the concentration might have been quite high.

## Atmospheric fate:

Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. In the ambient atmosphere, xylenes are expected to exist solely in the vapour phase. Xylenes are degraded in the atmosphere primarily by reaction with photochemically-produced hydroxyl radicals, with an estimated atmospheric lifetime of about 0.5 to 2 days. Xylenes' susceptibility to photochemical oxidation in the troposphere is to the extent that they may contribute to photochemical smog formation.

According to a model of gas/particle partitioning of semivolatile organic compounds in the atmosphere and from its vapour pressure, p-xylene, is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase p-xylene is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 16 hours. A half-life of 1.0 hr in summer and 10 hr in winter was measured for the reaction of p-xylene with photochemically-produced hydroxyl radicals. p-Xylene has a moderately high photochemical reactivity under smog conditions, higher than the other xylene isomers, with loss rates varying from 9-42% per hr. The photooxidation of p-xylene results in the production of carbon monoxide, formaldehyde, glyoxal, methylglyoxal, 3-methylbenzyl nitrate, m-tolualdehyde, 4-nitro-3-xylene, 5-nitro-3-xylene, 2,6-dimethyl-p-benzoquinone, 2,4-dimethylphenol, 6-nitro-2,4-dimethylphenol, 2,6-dimethylphenol, and 4-nitro-2,6-dimethylphenol.

## Ecotoxicity:

for xylenes

Fish LC50 (96 h) Pimephales promelas 13.4 mg/l; Oncorhynchus mykiss 8.05 mg/l; Lepomis macrochirus 16.1 mg/l (all flow through values); Pimephales promelas 26.7 (static)

Daphnia EC50 948 h): 3.83 mg/l

Photobacterium phosphoreum EC50 (24 h): 0.0084 mg/l

Gammarus lacustris LC50 (48 h): 0.6 mg/l.

## Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Atorn Bright Zinc 400ml		No data		
acetone	LOW	HIGH	LOW	HIGH
ethyl acetate	LOW	HIGH	MED	HIGH
xylene	LOW	LOW	LOW	

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 17 of 19

## Section 13 - DISPOSAL CONSIDERATIONS

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.
- Bury residues and emptied aerosol cans at an approved site.

## Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS  
HAZCHEM: 2YE (ADG7)

### ADG7:

Class or division:	2	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None
Special provisions:	63, 190, 277, 327	Packing Instructions:	None
Notes:	None	Limited quantities:	See SP 277
Portable tanks and bulk containers - Instructions:	None	Portable tanks and bulk containers - Special provisions:	None
Packagings and IBCs - Packing instruction:	P003, LP02	Packagings and IBCs - Special packing provisions:	PP17, PP87, L2

Shipping Name:AEROSOLS

### Land Transport UNDG:

Class or division:	2	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None

Shipping Name:AEROSOLS

### Air Transport IATA:

ICAO/IATA Class:	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	-
Special provisions:	A145		

Shipping Name: AEROSOLS, FLAMMABLE

### Maritime Transport IMDG:

IMDG Class:	2.1	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F- D, S- U	Special provisions:	63 190 277 327 959
Limited Quantities:	See SP277	Marine Pollutant:	Not Determined

Shipping Name: AEROSOLS

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 17-Nov-2009  
NC317ECP

CHEMWATCH 4744-39  
Version No:2.0  
CD 2009/3 Page 18 of 19

## Section 15 - REGULATORY INFORMATION

**POISONS SCHEDULE:** None

### REGULATIONS

Regulations for ingredients

#### **acetone (CAS: 67-64-1) is found on the following regulatory lists;**

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Illicit Drug Reagents/Essential Chemicals - Category III", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5", "GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "OECD Representative List of High Production Volume (HPV) Chemicals", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II"

#### **ethyl acetate (CAS: 141-78-6) is found on the following regulatory lists;**

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

#### **xylene (CAS: 1330-20-7) is found on the following regulatory lists;**

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

**No data for Atorn Bright Zinc 400ml (CW: 4744-39)**

## Section 16 - OTHER INFORMATION

### REPRODUCTIVE HEALTH GUIDELINES

■ Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
xylene	1.5 mg/m <sup>3</sup>	10	D	NA	-

■ These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined

continued...

# ATORN BRIGHT ZINC 400ML

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-39

Version No:2.0

CD 2009/3 Page 19 of 19

Section 16 - OTHER INFORMATION

---

by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 17-Nov-2009

Print Date: 17-Nov-2009

*This is the end of the MSDS.*