

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet
Issue Date: 17-Nov-2009
NC317ECP

CHEMWATCH 4744-41
Version No:2.0
CD 2009/3 Page 1 of 15

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ATORN GLASS CLEANER

SYNONYMS

"Manufacturer's Code .69357"

PROPER SHIPPING NAME

AEROSOLS

PRODUCT USE

■ Application is by spray atomisation from a hand held aerosol pack.
Window cleaner.

SUPPLIER

Company: Thomas Warburton Pty Ltd

Address:

16- 26 Dunlop Road

Mulgrave

VIC, 3170

AUS

Telephone: +61 3 9574 3400

Emergency Tel: +61 3 9547 3400

Fax: +61 3 9574 3456

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

DANGEROUS GOODS. NON-HAZARDOUS SUBSTANCE. According to NOHSC Criteria, and ADG Code.

POISONS SCHEDULE

None

RISK

- Extremely flammable.
- Risk of explosion if heated under confinement.

SAFETY

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/ fumes/ vapour/ spray.

- Avoid contact with skin.
- Wear eye/ face protection.
- In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
isopropanol	67-63-0	1-14
propylene glycol monomethyl ether - alpha isomer	107-98-2	1-5
d- limonene	5989-27-5	<0.25^
aliphatic hydrocarbons		5-15

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 2 of 15

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

citral	5392-40-5	N/S^
hydrocarbon propellant	68476-85-7.	N/S^

Section 4 - FIRST AID MEASURES

SWALLOWED

- Not considered a normal route of entry.

EYE

- If aerosols come in contact with the eyes:
 - Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If solids or aerosol mists are deposited upon the skin:
 - Flush skin and hair with running water (and soap if available).
 - Remove any adhering solids with industrial skin cleansing cream.
 - DO NOT use solvents.
 - Seek medical attention in the event of irritation.

INHALED

- If aerosols, fumes or combustion products are inhaled:
 - Remove to fresh air.
 - Lay patient down. Keep warm and rested.
 - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
 - Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- SMALL FIRE:
 - Water spray, dry chemical or CO2
- LARGE FIRE:
 - Water spray or fog.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 3 of 15

Section 5 - FIRE FIGHTING MEASURES

- Equipment should be thoroughly decontaminated after use.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition with violent container rupture.
 - Aerosol cans may explode on exposure to naked flames.
 - Rupturing containers may rocket and scatter burning materials.
 - Hazards may not be restricted to pressure effects.
 - May emit acrid, poisonous or corrosive fumes.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.
- WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 2YE

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Wipe up.
- If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Absorb or cover spill with sand, earth, inert materials or vermiculite.
- If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.
- Collect residues and seal in labelled drums for disposal.

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet
Issue Date: 17-Nov-2009
NC317ECP

CHEMWATCH 4744-41
Version No:2.0
CD 2009/3 Page 4 of 15

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	isopropanol (Isopropyl alcohol)	400	983	500	1230
Australia Exposure Standards	propylene glycol monomethyl ether -	100	369	150	553

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet
Issue Date: 17-Nov-2009
NC317ECP

CHEMWATCH 4744-41
Version No:2.0
CD 2009/3 Page 5 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	alpha isomer (Propylene glycol monomethyl ether) hydrocarbon propellant (LPG (liquified petroleum gas))	1000	1800		

The following materials had no OELs on our records

- d- limonene: CAS:5989- 27- 5 CAS:138- 86- 3
- citral: CAS:5392- 40- 5

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
isopropanol		2, 000 [LEL]

NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

MATERIAL DATA

ATORN GLASS CLEANER:
Not available

ISOPROPANOL:

- Odour Threshold Value: 3.3 ppm (detection), 7.6 ppm (recognition)

Exposure at or below the recommended isopropanol TLV-TWA and STEL is thought to minimise the potential for inducing narcotic effects or significant irritation of the eyes or upper respiratory tract. It is believed, in the absence of hard evidence, that this limit also provides protection against the development of chronic health effects. The limit is intermediate to that set for ethanol, which is less toxic, and n-propyl alcohol, which is more toxic, than isopropanol.

PROPYLENE GLYCOL MONOMETHYL ETHER - ALPHA ISOMER:

- for propylene glycol monomethyl ether (PGME)

Odour Threshold: 10 ppm.

The TLV-TWA is protective against discomfort caused by odour, against eye and skin irritation, and chronic effects (including possible liver and kidney damage).

Individuals exposed to 100 ppm reported a transient unpleasant odour with slight eye irritation after about 1 or 2 hours. At 300 ppm, mild irritation of the eyes and nose developed within 5 minutes; some individuals found the irritation hardly bearable after about an hour. A concentration of 750 ppm was highly irritating. Signs of central nervous system depression developed at 1000 ppm. Neurological, clinical chemical and general medical examinations showed no other conspicuous toxicity.

Concentrations of the beta-isomer, 2-methoxy-1-propyl acetate are low in commercial grades of PGME and teratogenic effects associated with this isomer are expected to be absent.

Odour Safety Factor(OSF)

OSF=10 (propylene glycol monomethyl ether).

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 6 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.
- For potentially heavy exposures:
- Wear chemical protective gloves, eg. PVC. and safety footwear.

OTHER

- No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

RESPIRATOR

- Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AX- AUS P	-
1000	50	-	AX- AUS P
5000	50	Airline *	-
5000	100	-	AX- 2 P
10000	100	-	AX- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.

Provide adequate ventilation in warehouse or closed storage areas.

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet
Issue Date: 17-Nov-2009
NC317ECP

CHEMWATCH 4744-41
Version No:2.0
CD 2009/3 Page 7 of 15

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

■ Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable hydrocarbon propellant. Turbid liquid spray with a lemon odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Gas.

Mixes with water.

Molecular Weight: Not Applicable	Boiling Range (°C): Not Available	Melting Range (°C): Not Available
Specific Gravity (water=1): 0.905	Solubility in water (g/L): Miscible	pH (as supplied): 9.5- 10.5
pH (1% solution): Not Available	Vapour Pressure (kPa): Not Available	Volatile Component (%vol): Not Available
Evaporation Rate: Not Available	Relative Vapour Density (air=1): Not Available	Flash Point (°C): Not Available
Lower Explosive Limit (%): 2.0	Upper Explosive Limit (%): 12.7	Autoignition Temp (°C): Not Available
Decomposition Temp (°C): Not Available	State: Liquid	Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
 - Presence of open flame.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments. Ingestion may result in nausea, abdominal irritation, pain and vomiting.

EYE

■ Not considered to be a risk because of the extreme volatility of the gas. Isopropanol vapour may cause mild eye irritation at 400 ppm. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Eye contact may cause tearing or blurring of vision. There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

SKIN

■ The material may accentuate any pre-existing dermatitis condition. Spray mist may produce discomfort. Open cuts, abraded or irritated skin should not be exposed to this material.

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 8 of 15

Section 11 - TOXICOLOGICAL INFORMATION

There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

INHALED

■ **WARNING:** Intentional misuse by concentrating/inhaling contents may be lethal.

The odour of isopropanol may give some warning of exposure, but odour fatigue may occur. Inhalation of isopropanol may produce irritation of the nose and throat with sneezing, sore throat and runny nose. The effects in animals subject to a single exposure, by inhalation, included inactivity or anaesthesia and histopathological changes in the nasal canal and auditory canal.

Spray mist may produce discomfort.

CHRONIC HEALTH EFFECTS

■ There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Long term or repeated ingestion exposure of isopropanol may produce incoordination, lethargy and reduced weight gain.

Repeated inhalation exposure to isopropanol may produce narcosis, incoordination and liver degeneration. Animal data show developmental effects only at exposure levels that produce toxic effects in the adult animals. Isopropanol does not cause genetic damage in bacterial or mammalian cell cultures or in animals.

There are inconclusive reports of human sensitisation from skin contact with isopropanol. Chronic alcoholics are more tolerant of systemic isopropanol than are persons who do not consume alcohol; alcoholics have survived as much as 500 ml. of 70% isopropanol.

Continued voluntary drinking of a 2.5% aqueous solution through two successive generations of rats produced no reproductive effects.

NOTE: Commercial isopropanol does not contain "isopropyl oil". An excess incidence of sinus and laryngeal cancers in isopropanol production workers has been shown to be caused by the byproduct "isopropyl oil".

Changes in the production processes now ensure that no byproduct is formed. Production changes include use of dilute sulfuric acid at higher temperatures.

WARNING: Aerosol containers may present pressure related hazards.

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

ISOPROPANOL:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 3570 mg/kg

Oral (human) TDL0: 223 mg/kg

Oral (man) TDL0: 14432 mg/kg

Oral (rat) LD50: 5045 mg/kg

Dermal (rabbit) LD50: 12800 mg/kg

■ For isopropanol (IPA):

Acute toxicity: Isopropanol has a low order of acute toxicity. It is irritating to the eyes, but not to the skin. Very high vapor concentrations are irritating to the eyes, nose, and throat, and prolonged exposure may produce central nervous system depression and narcosis. Human volunteers reported that exposure to 400 ppm isopropanol vapors for 3 to 5 min. caused mild irritation of the eyes, nose and throat.

Although isopropanol produced little irritation when tested on the skin of human volunteers, there have been reports of isolated cases of dermal irritation and/or sensitization. The use of isopropanol as a sponge treatment for the control of fever has resulted in cases of intoxication, probably the result of both dermal absorption and inhalation. There have been a number of cases of poisoning reported due to the intentional ingestion of isopropanol, particularly among alcoholics or suicide victims. These ingestions typically result in a comatose condition. Pulmonary difficulty, nausea, vomiting, and headache accompanied by various degrees of central nervous system depression are typical. In the absence of shock, recovery usually occurred.

IRRITATION

Skin (rabbit): 500 mg - Mild

Eye (rabbit): 10 mg - Moderate

Eye (rabbit): 100mg/24hr- Moderate

Eye (rabbit): 100 mg - SEVERE

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 9 of 15

Section 11 - TOXICOLOGICAL INFORMATION

Repeat dose studies: The systemic (non-cancer) toxicity of repeated exposure to isopropanol has been evaluated in rats and mice by the inhalation and oral routes. The only adverse effects-in addition to clinical signs identified

from these studies were to the kidney.

Reproductive toxicity: A recent two-generation reproductive study characterised the reproductive hazard for isopropanol associated with oral gavage exposure. This study found that the only reproductive parameter apparently affected by isopropanol exposure was a statistically significant decrease in male mating index of the F1 males. It is possible that the change in this reproductive parameter was treatment related and significant, although the mechanism of this effect could not be discerned from the results of the study.

However, the lack of a significant effect of the female mating index in either generation, the absence of any adverse effect on litter size, and the lack of histopathological findings of the testes of the high-dose males suggest that the observed reduction in male mating index may not be biologically meaningful.

Developmental toxicity: The developmental toxicity of isopropanol has been characterized in rat and rabbit developmental toxicity studies. These studies indicate that isopropanol is not a selective developmental hazard. Isopropanol produced developmental toxicity in rats, but not in rabbits. In the rat, the developmental toxicity occurred only at maternally toxic doses and consisted of decreased foetal body weights, but no teratogenicity

Genotoxicity: All genotoxicity assays reported for isopropanol have been negative

Carcinogenicity: rodent inhalation studies were conducted to evaluate isopropanol for cancer potential. The only tumor rate increase seen was for interstitial (Leydig) cell tumors in the male rats. Interstitial cell tumors of the testis is typically the most frequently observed spontaneous tumor in aged male Fischer 344 rats. These studies demonstrate that isopropanol does not exhibit carcinogenic potential relevant to humans. Furthermore, there was no evidence from this study to indicate the development of carcinomas of the testes in the male rat, nor has isopropanol been found to be genotoxic. Thus, the testicular tumors seen in the isopropanol exposed male rats are considered of no significance in terms of human cancer risk assessment. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

PROPYLENE GLYCOL MONOMETHYL ETHER - ALPHA ISOMER:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 3739 mg/kg

Inhalation (human) TClO: 3000 ppm

Inhalation (rat) LC50: 10000 ppm/5 h.

Dermal (rabbit) LD50: 13000 mg/kg

■ for propylene glycol ethers (PGEs):

Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM).

Testing of a wide variety of propylene glycol ethers Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on reproductive organs, the developing embryo and fetus, blood (haemolytic effects), or thymus, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces an alkoxyacetic acid. The reproductive and developmental toxicities of the lower molecular weight homologues in the ethylene series are due specifically to the formation of methoxyacetic and ethoxyacetic acids.

Longer chain length homologues in the ethylene series are not associated with the reproductive toxicity but can cause haemolysis in sensitive species, also through formation of an alkoxyacetic acid. The predominant alpha isomer of all the PGEs (thermodynamically favored during manufacture of PGEs) is a secondary alcohol incapable of forming an alkoxypropionic acid. In contrast beta-isomers are able to form the alkoxypropionic acids and these are linked to teratogenic effects (and possibly haemolytic effects).

This alpha isomer comprises greater than 95% of the isomeric mixture in the commercial product.

Because the alpha isomer cannot form an alkoxypropionic acid, this is the most likely reason for the lack of toxicity shown by the PGEs as distinct from the lower molecular weight ethylene glycol ethers. More importantly, however, very extensive empirical test data show that this class of commercial-grade glycol

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet
Issue Date: 17-Nov-2009
NC317ECP

CHEMWATCH 4744-41
Version No:2.0

CD 2009/3 Page 10 of 15

Section 11 - TOXICOLOGICAL INFORMATION

ether presents a low toxicity hazard. PGEs, whether mono, di- or tripropylene glycol-based (and no matter what the alcohol group), show a very similar pattern of low to non-detectable toxicity of any type at doses or exposure levels greatly exceeding those showing pronounced effects from the ethylene series. One of the primary metabolites of the propylene glycol ethers is propylene glycol, which is of low toxicity and completely metabolised in the body.

As a class, the propylene glycol ethers are rapidly absorbed and distributed throughout the body when introduced by inhalation or oral exposure. Dermal absorption is somewhat slower but subsequent distribution is rapid. Most excretion for PGEs is via the urine and expired air. A small portion is excreted in the faeces.

As a group PGEs exhibits low acute toxicity by the oral, dermal, and inhalation routes. Rat oral LD50s range from >3,000 mg/kg (PnB) to >5,000 mg/kg (DPMA). Dermal LD50s are all > 2,000 mg/kg (PnB, & DPnB; where no deaths occurred), and ranging up to >15,000 mg/kg (TPM). Inhalation LC50 values were higher than 5,000 mg/m³ for DPMA (4-hour exposure), and TPM (1-hour exposure). For DPnB the 4-hour LC50 is >2,040 mg/m³. For PnB, the 4-hour LC50 was >651 ppm (>3,412 mg/m³), representing the highest practically attainable vapor level. No deaths occurred at these concentrations. PnB and TPM are moderately irritating to eyes while the remaining category members are only slightly irritating to nonirritating. PnB is moderately irritating to skin while the remaining category members are slightly to non-irritating

None are skin sensitizers.

In repeated dose studies ranging in duration from 2 to 13 weeks, few adverse effects were found even at high exposure levels and effects that did occur were mild in nature. By the oral route of administration, NOAELs of 350 mg/kg-d (PnB – 13 wk) and 450 mg/kg-d (DPnB – 13 wk) were observed for liver and kidney weight increases (without accompanying histopathology). LOAELs for these two chemicals were 1000 mg/kg-d (highest dose tested).

Dermal repeated-dose toxicity tests have been performed for many PGEs. For PnB, no effects were seen in a 13-wk study at doses as high as 1,000 mg/kg-d. A dose of 273 mg/kg-d constituted a LOAEL (increased organ weights without histopathology) in a 13-week dermal study for DPnB. For TPM, increased kidney weights (no histopathology) and transiently decreased body weights were found at a dose of 2,895 mg/kg-d in a 90-day study in rabbits. By inhalation, no effects were observed in 2-week studies in rats at the highest tested concentrations of 3244 mg/m³ (600 ppm) for PnB and 2,010 mg/m³ (260 ppm) for DPnB. TPM caused increased liver weights without histopathology by inhalation in a 2-week study at a LOAEL of 360 mg/m³ (43 ppm). In this study, the highest tested TPM concentration, 1010 mg/m³ (120 ppm), also caused increased liver weights without accompanying histopathology. Although no repeated-dose studies are available for the oral route for TPM, or for any route for DPMA, it is anticipated that these chemicals would behave similarly to other category members.

One and two-generation reproductive toxicity testing has been conducted in mice, rats, and rabbits via the oral or inhalation routes of exposure on PM and PMA. In an inhalation rat study using PM, the NOAEL for parental toxicity is 300 ppm (1106 mg/m³) with decreases in body and organ weights occurring at the LOAEL of 1000 ppm (3686 mg/m³). For offspring toxicity the NOAEL is 1000 ppm (3686 mg/m³), with decreased body weights occurring at 3000 ppm (11058 mg/m³). For PMA, the NOAEL for parental and offspring toxicity is 1000 mg/kg/d. in a two generation gavage study in rats. No adverse effects were found on reproductive organs, fertility rates, or other indices commonly monitored in such studies. In addition, there is no evidence from histopathological data from repeated-dose studies for the category members that would indicate that these chemicals would pose a reproductive hazard to human health.

In developmental toxicity studies many PGEs have been tested by various routes of exposure and in various species at significant exposure levels and show no frank developmental effects. Due to the rapid hydrolysis of DPMA to DPM, DPMA would not be expected to show teratogenic effects. At high doses where maternal toxicity occurs (e.g., significant body weight loss), an increased incidence of some anomalies such as delayed skeletal ossification or increased 13th ribs, have been reported. Commercially available PGEs showed no teratogenicity.

The weight of the evidence indicates that propylene glycol ethers are not likely to be genotoxic. In vitro, negative results have been seen in a number of assays for PnB, DPnB, DPMA and TPM. Positive results were only seen in 3 out of 5 chromosome aberration assays in mammalian cells with DPnB. However, negative results were seen in a mouse micronucleus assay with DPnB and PM. Thus, there is no evidence to suggest these PGEs would be genotoxic in vivo. In a 2-year bioassay on PM, there were no statistically significant increases in tumors in rats and mice.

NOTE: For PGE - mixed isomers: Exposure of pregnant rats and rabbits to the substance did not give rise to teratogenic effects at concentrations up to 3000 ppm. Foetotoxic effects were seen in rats but not in rabbits at this concentration; maternal toxicity was noted in both species.

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 11 of 15

Section 11 - TOXICOLOGICAL INFORMATION

CARCINOGEN

Isopropanol	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3
-------------	---	-------	---

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

ATORN GLASS CLEANER:

PROPYLENE GLYCOL MONOMETHYL ETHER - ALPHA ISOMER:

ISOPROPANOL:

- DO NOT discharge into sewer or waterways.

ATORN GLASS CLEANER:

- WGK: Classification in accordance with German Water Resources Act.

Water hazard class 1: slightly hazardous to water.

ISOPROPANOL:

■ log Kow (Sangster 1997):	0.05
■ log Pow (Verschueren 1983):	- 0.5714285
■ BOD5:	60%
■ BOD20:	78%
■ COD:	2.23
■ ThOD:	2.4
■ Half- life Soil - High (hours):	168
■ Half- life Soil - Low (hours):	24
■ Half- life Air - High (hours):	72
■ Half- life Air - Low (hours):	6.2
■ Half- life Surface water - High (hours):	168
■ Half- life Surface water - Low (hours):	24
■ Half- life Ground water - High (hours):	336
■ Half- life Ground water - Low (hours):	48
■ Aqueous biodegradation - Aerobic - High (hours):	168
■ Aqueous biodegradation - Aerobic - Low (hours):	24
■ Aqueous biodegradation - Anaerobic - High (hours):	672
■ Aqueous biodegradation - Anaerobic - Low (hours):	96
■ Photooxidation half- life water - High (hours):	1.90E+05
■ Photooxidation half- life water - Low (hours):	4728
■ Photooxidation half- life air - High (hours):	72
■ Photooxidation half- life air - Low (hours):	6.2

- For isopropanol (IPA):

log Kow : -0.16- 0.28

Half-life (hr) air: 33-84

Half-life (hr) H2O surface water: 130

Henry's atm m3 /mol: 8.07E-06

BOD 5: 1.19,60%

COD : 1.61-2.30,97%

ThOD : 2.4

BOD 20: >70% * [Akzo Nobel]

Environmental Fate

Based on calculated results from a lever 1 fugacity model,IPA is expected to partition primarily to the aquatic compartment (77.7%) with the remainder to the air (22.3%). IPA has been shown to biodegrade rapidly in aerobic, aqueous biodegradation tests and therefore, would not be expected to persist in aquatic habitats.

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 12 of 15

Section 12 - ECOLOGICAL INFORMATION

IPA is also not expected to persist in surface soils due to rapid evaporation to the air. In the air, physical degradation will occur rapidly due to hydroxy radical (OH) attack. Overall, IPA presents a low potential hazard to aquatic or terrestrial biota. IPA is expected to volatilise slowly from water based on a calculated Henry's Law constant of 7.52×10^{-6} atm.m³/mole. The calculated half-life for the volatilisation from surface water (1 meter depth) is predicted to range from 4 days (from a river) to 31 days (from a lake). Hydrolysis is not considered a significant degradation process for IPA. However, aerobic biodegradation of IPA has been shown to occur rapidly under non-acclimated conditions, based on a result of 49% biodegradation from a 5 day BOD test. Additional biodegradation data developed using standardized test methods show that IPA is readily biodegradable in both freshwater and saltwater media (72 to 78% biodegradation in 20 days). IPA will evaporate quickly from soil due to its high vapor pressure (43 hPa at 20°C), and is not expected to partition to the soil based on a calculated soil adsorption coefficient (log K_{oc}) of 0.03. IPA has the potential to leach through the soil due to its low soil adsorption. In the air, isopropanol is subject to oxidation predominantly by hydroxy radical attack. The room temperature rate constants determined by several investigators are in good agreement for the reaction of IPA with hydroxy radicals. The atmospheric half-life is expected to be 10 to 25 hours, based on measured degradation rates ranging from 5.1 to 7.1×10^{-12} cm³/molecule-sec, and an OH concentration of 1.5×10^6 molecule/cm³, which is a commonly used default value for calculating atmospheric half-lives. Using OH concentrations representative of polluted (3×10^6) and pristine (3×10^5) air, the atmospheric half-life of IPA would range from 9 to 126 hours, respectively. Direct photolysis is not expected to be an important transformation process for the degradation of IPA.

Ecotoxicity:

IPA has been shown to have a low order of acute aquatic toxicity. Results from 24- to 96-hour LC₅₀ studies range from 1,400 to more than 10,000 mg/L for freshwater and saltwater fish and invertebrates. In addition, 16-hour to 8-day toxicity threshold levels (equivalent to 3% inhibition in cell growth) ranging from 104 to 4,930 mg/L have been demonstrated for various microorganisms.

Chronic aquatic toxicity has also been shown to be of low concern, based on 16- to 21-day NOEC values of 141 to 30 mg/L, respectively, for a freshwater invertebrate. Bioconcentration of IPA in aquatic organisms is not expected to occur based on a measured log octanol/water partition coefficient (log K_{ow}) of 0.05, a calculated bioconcentration factor of 1 for a freshwater fish, and the unlikelihood of constant, long-term exposures.

Toxicity to Plants

Toxicity of IPA to plants is expected to be low, based on a 7-day toxicity threshold value of 1,800 mg/L for a freshwater algae, and an EC₅₀ value of 2,100 mg/L from a lettuce seed germination test.

PROPYLENE GLYCOL MONOMETHYL ETHER - ALPHA ISOMER:

■ For glycol ethers:

Environmental fate:

Ether groups are generally stable to hydrolysis in water under neutral conditions and ambient temperatures. OECD guideline studies indicate ready biodegradability for several glycol ethers although higher molecular weight species seem to biodegrade at a slower rate. No glycol ethers that have been tested demonstrate marked resistance to biodegradative processes. Upon release to the atmosphere by evaporation, high boiling glycol ethers are estimated to undergo photodegradation (atmospheric half lives = 2.4-2.5 hr). When released to water, glycol ethers undergo biodegradation (typically 47-92% after 8-21 days) and have a low potential for bioaccumulation (log K_{ow} ranges from -1.73 to +0.51).

Ecotoxicity:

Aquatic toxicity data indicate that the tri- and tetra ethylene glycol ethers are "practically non-toxic" to aquatic species. No major differences are observed in the order of toxicity going from the methyl- to the butyl ethers.

Glycols exert a high oxygen demand for decomposition and once released to the environments cause the death of aquatic organisms if dissolved oxygen is depleted.

■ for propylene glycol ethers:

Environmental fate:

Most are liquids at room temperature and all are water-soluble.

Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM)

Environmental fate: Log octanol-water partition coefficients (log K_{ow}'s) range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation. Henry's Law Constants, which indicate propensity to partition from water to air, are low for all category members, ranging from 5.7×10^{-9} atm-m³/mole for TPM to 2.7×10^{-9} atm-m³/mole for PnB. Fugacity modeling

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 13 of 15

Section 12 - ECOLOGICAL INFORMATION

indicates that most propylene glycol ethers are likely to partition roughly equally into the soil and water compartments in the environment with small to negligible amounts remaining in other environmental compartments (air, sediment, and aquatic biota). Propylene glycol ethers are unlikely to persist in the environment. Once in air, the half-life of the category members due to direct reactions with photochemically generated hydroxyl radicals, range from 2.0 hours for TPM to 4.6 hours for PnB. In water, most this family are "readily biodegradable" under aerobic conditions. (DPMA degraded within 28 days (and within the specified 10-day window) but only using pre-adapted or "acclimated" inoculum.). In soil, biodegradation is rapid for PM and PMA.

Ecotoxicity:

Acute aquatic toxicity testing indicates low toxicity for both ethers and acetates. For ethers, effect concentrations are > 500 mg/L. For acetates, effect concentrations are > 151 mg/L.

log Kow: -0.53

Dissolves rapidly in water; the material is volatile and will partition to the air compartment.

Readily biodegradable.

Degradation by activated sludge in 29 days=90%

Not expected to bioaccumulate

Fish LC50 (96 h): fathead minnow >2000 mg/l

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Atorn Glass Cleaner		No data		
isopropanol	LOW	MED	LOW	HIGH
propylene glycol	LOW	LOW	LOW	HIGH
monomethyl ether - alpha isomer				

Section 13 - DISPOSAL CONSIDERATIONS

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.
- Bury residues and emptied aerosol cans at an approved site.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS

HAZCHEM: 2YE (ADG7)

ADG7:

Class or division:	2	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None
Special provisions:	63, 190, 277, 327	Packing Instructions:	None
Notes:	None	Limited quantities:	See SP 277
Portable tanks and bulk containers -	None	Portable tanks and bulk containers - Special	None

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 14 of 15

Section 14 - TRANSPORTATION INFORMATION

Instructions:

Packagings and IBCs - P003, LP02

Packing instruction:

provisions:

Packagings and IBCs - PP17, PP87, L2

Special packing

provisions:

Shipping Name:AEROSOLS

Land Transport UNDG:

Class or division: 2

UN No.: 1950

Shipping Name:AEROSOLS

Subsidiary risk: None

UN packing group: None

Air Transport IATA:

ICAO/IATA Class: 2.1

UN/ID Number: 1950

Special provisions: A145

Shipping Name: AEROSOLS, FLAMMABLE

ICAO/IATA Subrisk: None

Packing Group: -

Maritime Transport IMDG:

IMDG Class: 2.1

UN Number: 1950

EMS Number: F- D, S- U

Limited Quantities: See SP277

Shipping Name: AEROSOLS

IMDG Subrisk: SP63

Packing Group: None

Special provisions: 63 190 277 327 959

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

Regulations for ingredients

isopropanol (CAS: 67-63-0) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "OECD Representative List of High Production Volume (HPV) Chemicals"

propylene glycol monomethyl ether - alpha isomer (CAS: 107-98-2) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Atorn Glass Cleaner (CW: 4744-41)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name

d- limonene

hydrocarbon propellant

CAS

5989- 27- 5, 138- 86- 3

68476- 85- 7, 68476- 86- 8

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

continued...

ATORN GLASS CLEANER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Nov-2009

NC317ECP

CHEMWATCH 4744-41

Version No:2.0

CD 2009/3 Page 15 of 15

Section 16 - OTHER INFORMATION

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 17-Nov-2009

Print Date: 17-Nov-2009

This is the end of the MSDS.